



APSI 300 compact

Automatic coil inserting machine aimed for the digital print market. Inserts pre-cut lengths of coil into the pre-punched book blocks. For all types of plastic coil book production.



Customer benefits:

- Automatic insertion of pre-cut coil
- 0.2475" pitch
- Pre-set crimping of both ends simultaneously
- Quick adjustment for high flexibility of different product formats
- No tools required for basic setup and changeover
- Vertical book placement can accommodate tabs

Maximum:

 Width
297 mm

 Bind up to
15,6 mm

Output:


 Max. bound
products per hour
450





Built in coil sizing gauge.

The APSI 300 compact offers a built in coil sizing gauge to help the operator confirm the diameter of coil required in relation to the book's thickness.



Vertical book placement.

The APSI 300 compact has gravity working to its advantage. The pre-punched book is positioned in the machine on its spine meaning that tabs or wider covers are no problem.



Coil diameter changeover

The APSI 300 compact does not require tools for basic setup and changeover. The APSI innovative coil diameter adjustment provides easy and accurate positioning.

Note: 8 mm coil is the smallest diameter that can be used.



Built-in spine former storage.

Spine formers are what the pre-punched book sits on when it is positioned in the machine. The spine formers correspond to the diameter of coil being used. The spine formers are stored securely within the machine.



The APSI 300 compact model has a LCD screen that guides the operator through the machine's setup and operation. The screen communicates the machine's status at all times.

Technical data:	APSI 300 compact
Pitch:	0.2475"
Binding thickness:	5 - 15,6 mm
Binding element Ø:	8 - 20 mm
Min. binding width:	100 mm
Max. binding width:	297 mm
Min. unbound edge:	140 mm
Max. unbound edge:	500 mm
Binding operation:	Electric insert, cut & crimp
No. of books output per hr:	450
Time required for diameter change:	5 min
Format change without diameter:	2 min
Machine dimensions L x W x H:	780 x 560 x 380 mm
Machine weight:	61 kg
Machine packaging dimensions L x W x H:	910 x 610 x 560 mm
Machine weight with packaging:	105 kg
Compressed air:	No
Power requirement:	220V/1.4Amps 215V/2.0Amps

Technical modifications may be made without notice.

All performance outputs are based on 80 gsm paper and may vary depending on the product type, the working environment and the operator.

For further information and videos please visit: